1.B.2.c - Venting and Flaring

## 1.B.2.c - Flaring

<b>Category Code</b>		Method				AD				EF					
1.B.2.c		T2				AS				CS					
<b>Key Category</b>	SO <sub>2</sub>	NOx	ΝНз	NMVOC	CO	ВС	Pb	Hg	Cd	Diox	PAH	НСВ	TSP	PM <sub>10</sub>	PM <sub>2</sub> 5
1.B.2.c	-/-	-/-	-	-/-	-/-	-/-	-	-/-	-	-	-	-	-/-	-/-	-/-

Pursuant to general requirements of the Technical Instructions on Air Quality Control TA Luft (2002), gases, steam, hydrogen and hydrogen sulphide released from pressure valves and venting equipment must be collected in a gas-collection system. Wherever possible, gases so collected are burned in process combustion. Where such use is not possible, the gases are piped to a flare. Flares used for flaring of such gases must fulfill at least the requirements for flares for combustion of gases from operational disruptions and from safety valves. For refineries and other types of plants in categories 1.B.2, flares are indispensable safety components. In crude-oil refining, excessive pressures can build up in process systems, for various reasons. Such excessive pressures have to be reduced via safety valves, to prevent tanks and pipelines from bursting. Safety valves release relevant products into pipelines that lead to flares. Flares carry out controlled burning of gases released via excessive pressures. When in place, flare-gas recovery systems liquify the majority of such gases and return them to refining processes or to refinery combustion systems. In the process, more than 99 % of the hydrocarbons in the gases are converted to CO2 and H2O. When a plant has such systems in operation, its flarehead will seldom show more than a small pilot flame.

	Unit	1990	1995	2000	2005	2010	2015	2018	2019
Flared natural gas	millions of m <sup>3</sup>	36	33	36	18.7	12.1	10.5	10.6	15.6
Refined crude-oil quantity	millions of t	107	96.5	107.6	114.6	95.4	93.4	87.7	87

Flaring takes place in extraction and pumping systems and at refineries. In refineries, flaring operations are subdivided into regular operations and start-up / shut-down operations in connection with disruptions.

Source of emission factor	Substa	nce	Jnit		Value			
Flaring emissions in natural gas extraction	NMVOC	ŀ	kg/ 1000	) m³	0.005			
Flaring emissions in natural gas extraction NO <sub>x</sub>			kg/ 1000	) m³	1.269			
Flaring emissions in natural gas extraction SO <sub>2</sub>			kg/ 1000	) m³	8.885			
Flaring emissions in natural gas extraction	gas extraction CO			) m³	0.726			
Source of emission factor			stance	Unit	Value	غ		
Flaring emissions at petroleum production facilities N			OC	kg/m	า³ 0.157	7		
Flaring emissions at petroleum production	Flaring emissions at petroleum production facilities NC				0.008	3		
Flaring emissions at petroleum production	SO <sub>2</sub>	₂ kg/t		0.010	)			
Flaring emissions at petroleum production	CO		kg/t	0				
Source of emission factor			Subst	ance	Unit	Valu	ıe	
Flaring emissions at refineries: normal flaring operations			s NMV	OC.	kg/m³	0.00	)4	
Flaring emissions at refineries: normal flaring operations				)	kg/m³	0.00	)1	
Flaring emissions at refineries: normal flaring operations				SO <sub>2</sub>		0.00	)3	
Flaring emissions at refineries: normal flaring operations				NO <sub>×</sub> kg/		0		
Source of emission factor					Substance		Valu	e
Flaring emissions at refineries: disruptions of flaring operations					OC	kg/t	0.00	1
Flaring emissions at refineries: disruptions of flaring operations						kg/t	0.00	1

Flaring emissions at refineries: disruptions of flaring operations	SO2	kg/t	0.007
Flaring emissions at refineries: disruptions of flaring operations	NOx	kg/t	0.004

The emission factors have been derived from the 2004 and 2008 emissions declarations Theloke et al. 2013 [1]. In 2019, they were updated for CH4, N2O, CO, NMVOC, NOx and SO2, on the basis of Bender & von Müller, 2019 [2]. Venting emissions are taken into account in category 1.B.2.b.iii. The SO2 emissions are obtained from the activity data for the flared natural gas (Table 178) and an emission factor of 0.140 kg /  $1,000 \text{ m}^3$ , a factor which takes account of an average H2S content of 5 % by volume. The emission factors are determined on the basis of emissions reports, crude-oil-refining capacity and total capacity utilisation at German refineries. The guide for this work consists of the evaluation assessment of Theloke et al. (2013) [1].

## References

- [1] Theloke, J., Kampffmeyer, T., Kugler, U., Friedrich, R., Schilling, S., Wolf, L., & Springwald, T. (2013). Ermittlung von Emissionsfaktoren und Aktivitätsraten im Bereich IPCC (1996) 1.B.2.a. i-vi Diffuse Emissionen aus Mineralöl und Mineralölprodukten (Förderkennzeichen 360 16 033). Stuttgart.
- [2] Bender, M., & von Müller, G. (2019). Konsolidierung der Treibhausgasemissionsberechnungen unter der 2. Verpflichtungsperiode des Kyoto-Protokolls und der neuen Klimaschutz-Berichterstattungs-pflichten an die EU (FKZ 3716 41 107 0).