

## 2.D.3.b - Road Paving

### Short description

Category Code	Method					AD					EF				
2.D.3.b	T1					AS					CS				
Key Category	SO <sub>2</sub>	NO <sub>x</sub>	NH <sub>3</sub>	NMVOC	CO	BC	Pb	Hg	Cd	Diox	PAH	HCB	TSP	PM <sub>10</sub>	PM <sub>2.5</sub>
2.D.3.b	-/-	-/-	-	-/-	-	-	-	-	-	-	-	-	-/-	-/-	-/-

**T** = key source by Trend **L** = key source by Level

#### Methods

<b>D</b>	Default
<b>RA</b>	Reference Approach
<b>T1</b>	Tier 1 / Simple Methodology *
<b>T2</b>	Tier 2*
<b>T3</b>	Tier 3 / Detailed Methodology *
<b>C</b>	CORINAIR
<b>CS</b>	Country Specific
<b>M</b>	Model

\* as described in the EMEP/CORINAIR Emission Inventory Guidebook - 2007, in the group specific chapters.

#### AD - Data Source for Activity Data

<b>NS</b>	National Statistics
<b>RS</b>	Regional Statistics
<b>IS</b>	International Statistics
<b>PS</b>	Plant Specific data
<b>AS</b>	Associations, business organisations
<b>Q</b>	specific questionnaires, surveys

#### EF - Emission Factors

<b>D</b>	Default (EMEP Guidebook)
<b>C</b>	Confidential
<b>CS</b>	Country Specific
<b>PS</b>	Plant Specific data

Currently, the report tables list produced quantities of mixed asphalt products (from stationary installations only) and NMVOC, NO<sub>x</sub> and SO<sub>2</sub> emissions caused of this. Only emissions from asphalt production are reported. Figures relative to emissions released during laying of asphalt have not been examined.

### Method

## Activity data

The applicable quantity of mixed asphalt products produced (activity rate) has been taken from communications of the Deutscher Asphaltverband (DAV; German asphalt association). In total about 660 asphalt-mixing plants produce more than 40 Million tonnes of hot-mix for road paving [1].

## Emission factors

Emission factors have been determined country-specifically, pursuant to Tier 2. For determination of emission factors for emissions measurements from over 400 asphalt-mixing plants, made during the period 1989 through 2000, were used. The majority of the emissions occur during drying of pertinent mineral substances. Almost all of the NMVOC emissions originate in the organic raw materials used, and they are released primarily in parallel-drum operation, as well as from mixers and loading areas. On average, about 50% of the NO<sub>x</sub> and SO<sub>2</sub> involved come from the mineral substances (proportional process emissions). CO emissions are calculated solely in connection with fuel inputs.

Table 1: Overview of applied emission factors, in kg/t

<b>pollutant</b>	<b>Name of Category</b>	<b>EF value</b>	<b>EF trend</b>
<b>NMVOC</b>	Production of mixed asphalt	0.030	constant
<b>NO<sub>x</sub></b>	Production of mixed asphalt	0.015	constant
<b>SO<sub>x</sub></b>	Production of mixed asphalt	0.030	constant
<b>TSP</b>	Production of mixed asphalt	0.006	constant
<b>PM<sub>10</sub></b>	Production of mixed asphalt	0.0057	constant
<b>PM<sub>2.5</sub></b>	Production of mixed asphalt	0.003	constant

## Recalculations

With activity data and emission factors remaining unrevised, no recalculations have been carried out compared to last year's submission.

## Planned improvements

At the moment, no category-specific improvements are planned.