

1.A.3.b iii - Transport: Road Transport: Heavy Duty Vehicles and Buses

Short description

In sub-category 1.A.3.b iii - Road Transport: Heavy Duty Vehicles and Buses emissions from fuel combustion in trucks, lorries, buses etc. are reported.

Category Code	Method					AD					EF				
1.A.3.b iii	T1, T3					NS, M					CS, M, D				
Key Category	SO ₂	NO _x	NH ₃	NMVO	CO	BC	Pb	Hg	Cd	Diox	PAH	HC	TSP	PM ₁₀	PM _{2.5}
1.A.3.b iii	-/-	L/T	-/-	-/-	-/-	L/T	-/-	-/-	-/-	-/-	-/-	-	-/-	L/T	L/T

T = key source by Trend **L** = key source by Level

Methods

D	Default
RA	Reference Approach
T1	Tier 1 / Simple Methodology *
T2	Tier 2*
T3	Tier 3 / Detailed Methodology *
C	CORINAIR
CS	Country Specific
M	Model

* as described in the EMEP/CORINAIR Emission Inventory Guidebook - 2007, in the group specific chapters.

AD - Data Source for Activity Data

NS	National Statistics
RS	Regional Statistics
IS	International Statistics
PS	Plant Specific data
AS	Associations, business organisations
Q	specific questionnaires, surveys

EF - Emission Factors

D	Default (EMEP Guidebook)
C	Confidential
CS	Country Specific
PS	Plant Specific data

Methodology

Activity data

Specific consumption data for heavy-duty vehicles (trucks and lorries) and buses are generated within TREMOD ¹⁾. - The following tables provide an overview of annual amounts of fuels consumed by these vehicles in Germany.






Table 1: Annual fuel consumption of trucks and lorries, in terajoules

	1990	1995	2000	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019
HDVs: Buses																		
Diesel oil	57.433	49.083	49.344	39.968	39.501	37.437	38.906	42.223	44.623	44.276	47.546	48.820	46.298	49.575	51.430	50.676	48.797	50.087
Biodiesel	0	77	547	2.671	4.763	5.009	3.876	3.411	3.421	3.089	3.356	2.895	2.845	2.712	2.727	2.705	2.836	2.852
CNG	0	0	0	1.183	1.682	1.965	2.072	2.255	2.200	2.011	2.157	1.719	1.653	1.574	1.198	1.009	937	866
Biogas	0	0	0	0	0	0	0	0	0	0	308	340	417	265	282	314	252	396
Petroleum	0	610	414	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Σ Buses	57.433	49.159	49.891	43.822	45.946	44.411	44.854	47.889	50.244	49.376	53.366	53.775	51.213	54.127	55.637	54.704	52.822	54.201
HDVs: Trucks & Lorries																		
Diesel oil	401.691	541.176	630.955	486.102	508.241	491.992	496.253	482.997	526.385	527.113	550.718	566.541	539.595	558.842	564.107	567.943	553.039	563.811
Biodiesel	0	844	6.990	32.484	61.279	65.825	49.441	39.020	40.356	36.778	38.867	33.599	33.159	30.569	29.906	30.319	32.147	32.102
CNG	0	0	0	0	0	0	0	0	0	0	395	338	314	272	192	164	167	194
Biogas	0	0	0	0	0	0	0	0	0	0	56	67	79	46	45	51	45	89
Σ Trucks & Lorries	401.691	542.020	637.944	518.587	569.520	557.816	545.694	522.017	566.741	563.891	590.037	600.544	573.147	589.729	594.250	598.477	585.398	596.196
HDVs over all																		
Diesel oil	459.124	590.259	680.299	526.071	547.742	529.429	535.158	525.220	571.008	571.389	598.264	615.361	585.893	608.417	615.537	618.619	601.836	613.898
Biodiesel	0	921	7.537	35.155	66.042	70.833	53.317	42.432	43.777	39.867	42.223	36.494	36.004	33.281	32.633	33.025	34.984	34.954
CNG	0	0	0	1.183	1.682	1.965	2.072	2.255	2.200	2.011	2.552	2.057	1.967	1.846	1.390	1.173	1.104	1.060
Biogas	0	0	0	0	0	0	0	0	0	0	365	407	496	311	327	365	297	485
Petroleum	0	610	414	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Σ 1.A.3.b iii	459.124	591.179	687.835	562.409	615.465	602.227	590.547	569.906	616.985	613.267	643.403	654.319	624.360	643.855	649.887	653.181	638.221	650.396

source: TREMOD 6.02 ²⁾

gallery size="medium" : 1A3biii_AD.png gallery

[!- f<image LKW.PNG size="small"

gallery size="medium" : 1A3biii_AD_SNF.png gallery

f<image bus.PNG size="small"

gallery size="medium" : 1A3biii_AD_Bus.png : 1A3biii_AD_CNG.png gallery

-]



For information on mileage, please refer to sub-chapters on emissions from [tyre & brake wear and road abrasion](#).

Emission factors

The majority of emission factors for exhaust emissions from road transport are taken from the 'Handbook Emission Factors for Road Transport' (HBEFA, version 4.1) ³⁾ where they are provided on a tier3 level mostly and processed within the TREMOD software used by the party ⁴⁾.

However, it is not possible to present these tier3 values in a comprehensible way here.



With respect to the country-specific emission factors applied for particulate matter, given the circumstances during test-bench measurements, condensables are most likely included at least partly. ¹⁾

For heavy-metal (other than lead from leaded gasoline) and PAH exhaust-emissions, default emission factors from the 2019 EMEP Guidebook (EMEP/EEA, 2019) ⁵⁾ have been applied. Regarding PCDD/F, tier1 EF from (Rentz et al., 2008) ⁶⁾ are used instead.

Table 2: tier1 EF derived from default values

	Pb	Cd	Hg	As	Cr	Cu	Ni	Se	Zn	B[a]P	B[b]F	B[k]F	I[...]	PAH 1-4	PCDD/F
	[g/TJ]									[mg/TJ]					[µg/km]
Diesel oil	0.012	0.001	0.123	0.002	0.198	0.133	0.005	0.002	0.419	498	521	275	493	1,788	
Biodiesel	0.013	0.001	0.142	0.003	0.228	0.153	0.005	0.003	0.483	575	601	317	569	2,062	
CNG & Biogas	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	
Petroleum	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	
all fuels: buses															0.000019
all fuels: trucks & lorries															0.000016

Discussion of emission trends

NFR 1.A.3.b iii is key category for **NO_x**, **PM_{2.5}**, **PM₁₀**, and **BC**.

++ Nitrogen oxides (NO_x)

Until 2005, NO_x emissions followed mileage and fuel consumption. Since 2006, in contrast to nearly unchanged fuel consumption, emissions have decreased due to controlled catalytic-converter use and engine improvements resulting from continual tightening of emissions laws.

[gallery size="medium" : 1A3biii_EM_NOx.PNG](#) [gallery](#)

++ Non-methane volatile organic compounds (NMVOC) and carbon monoxide (CO)

Since the early 1990s, exhaust emissions of **NMVOC** and **carbon monoxide** have decreased due to catalytic-converter use and engine improvements resulting from ongoing tightening of emissions laws and improved fuel quality.

[gallery size="medium" : 1A3biii_EM_NMVOC.png](#) : [1A3biii_EM_CO.png](#) [gallery](#)

++ Ammonia (NH₃) and sulphur dioxide (SO₂)

As for the entire road transport sector, the trends for **sulphur dioxide** (SO₂) and **ammonia** (NH₃) exhaust emissions from heavy duty vehicles show characteristics different from those shown above: Here, the strong dependence on increasing fuel qualities (sulphur content) leads to an cascaded downward trend of SO₂ emissions, influenced only slightly by increases in fuel consumption and mileage. For **ammonia** emissions the increasing use of catalytic converters in gasoline driven cars in the 1990s lead to a steep increase whereas both the technical development of the converters and the ongoing shift from gasoline to diesel cars resulted in decreasing emissions in the following years.

[gallery size="medium" : 1A3biii_EM_SO2.png](#) : [1A3biii_EM_NH3.png](#) [gallery](#)

++ Particulate matter (BC, PM_{2.5}, PM₁₀, and TSP)

As for all reported exhaust PM emissions from mobile diesel vehicles the Party assumes that nearly all particles emitted are within the PM_{2.5} range, resulting in similar emission values for PM_{2.5}, PM₁₀, and TSP.

[gallery size="medium" : 1A3biii_EM_PM.PNG](#) [gallery](#)

Recalculations

Compared to submission 2020, recalculations were carried out due to a routine revision of the TREMOD software and the revision of several National Energy Balances (NEB).

Here, **activity data** were revised within TREMOD due to the provision of the final NEB 2018.

Furthermore, significant re-allocations of consumption shares between the different vehicle types and classes were conducted, effecting the entire time series but with the 1.A.3.b consumption totals remaining unaltered.

Table 4: Revised fuel consumption data, in terajoules

	1990	1995	2000	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018
DIESEL OIL																	
Submission 2021	23,131	19,972	24,124	23,030	21,811	21,678	20,902	20,202	19,039	18,591	17,555	17,548	17,996	17,777	18,080	18,456	
Submission 2020	22,049	16,628	19,184	20,151	20,306	17,167	17,492	17,657	17,384	18,033	17,840	18,540	19,289	18,641	18,609	18,809	
absolute change	1,082	3,344	4,940	2,878	1,505	4,511	3,410	2,544	1,655	558	-285	-992	-1,293	-863	-529	-352	
relative change	4,91%	20,1%	25,8%	14,3%	7,41%	26,3%	19,5%	14,4%	9,52%	3,09%	-1,60%	-5,35%	-6,71%	-4,63%	-2,84%	-1,87%	
BIODIESEL																	
Submission 2021	0	0	0	158	314	293	400	577	736	762	778	752	783	771	785	778	
Submission 2020	0	0	0	138	293	232	334	504	672	739	791	795	839	808	808	801	
absolute change	0	0	0	20	22	61	65	73	64	23	-13	-43	-56	-37	-23	-23	
relative change	0.00	0.00	0.00	14,3%	7,41%	26,3%	19,5%	14,4%	9,52%	3,09%	-1,60%	-5,35%	-6,71%	-4,63%	-2,84%	-2,82%	
CNG																	
Submission 2021	23,131	19,972	24,124	23,030	21,811	21,678	20,902	20,202	19,039	18,591	17,555	17,548	17,996	17,777	18,080	18,456	
Submission 2020	22,049	16,628	19,184	20,151	20,306	17,167	17,492	17,657	17,384	18,033	17,840	18,540	19,289	18,641	18,609	18,809	
absolute change	1,082	3,344	4,940	2,878	1,505	4,511	3,410	2,544	1,655	558	-285	-992	-1,293	-863	-529	-352	
relative change	4,91%	20,1%	25,8%	14,3%	7,41%	26,3%	19,5%	14,4%	9,52%	3,09%	-1,60%	-5,35%	-6,71%	-4,63%	-2,84%	-1,87%	
BIOGAS																	
Submission 2021	23,131	19,972	24,124	23,030	21,811	21,678	20,902	20,202	19,039	18,591	17,555	17,548	17,996	17,777	18,080	18,456	
Submission 2020	22,049	16,628	19,184	20,151	20,306	17,167	17,492	17,657	17,384	18,033	17,840	18,540	19,289	18,641	18,609	18,809	
absolute change	1,082	3,344	4,940	2,878	1,505	4,511	3,410	2,544	1,655	558	-285	-992	-1,293	-863	-529	-352	
relative change	4,91%	20,1%	25,8%	14,3%	7,41%	26,3%	19,5%	14,4%	9,52%	3,09%	-1,60%	-5,35%	-6,71%	-4,63%	-2,84%	-1,87%	
TOTAL FUEL CONSUMPTION																	
Submission 2021	23,131	19,972	24,124	23,188	22,125	21,971	21,302	20,779	19,775	19,354	18,336	18,304	18,783	18,554	18,871	19,242	
Submission 2020	22,049	16,628	19,184	20,290	20,598	17,399	17,827	18,162	18,056	18,773	18,631	19,335	20,128	19,449	19,417	19,609	
absolute change	1,082	3,344	4,940	2,898	1,527	4,572	3,475	2,617	1,719	581	-295	-1,030	-1,345	-895	-545	-368	
relative change	4.91%	20.1%	25.8%	14.3%	7.41%	26.3%	19.5%	14.4%	9.52%	3.09%	-1.58%	-5.33%	-6.68%	-4.60%	-2.81%	-1.88%	

Due to the variety of highly specific tier3 **emission factors** applied, it is not possible to display any changes in these data sets in a comprehensible way.



For more information on recalculated emission estimates reported for Base Year and 2018, please see the pollutant-specific recalculation tables following chapter [8.1 - Recalculations](#).

Planned improvements

Besides a routine revision of the underlying model, no specific improvements are planned.

FAQs

bibliography : 1 : Knörr et al. (2019a): Knörr, W., Heidt, C., Gores, S., & Bergk, F.: ifeu Institute for Energy and Environmental Research (Institut für Energie- und Umweltforschung Heidelberg gGmbH, ifeu): Fortschreibung des Daten- und Rechenmodells: Energieverbrauch und Schadstoffemissionen des motorisierten Verkehrs in Deutschland 1960-2030, sowie TREMOD, im Auftrag des Umweltbundesamtes, Heidelberg & Berlin, 2019. : 2 : Keller et al. (2007): Keller, M., Hausberger, S., Matzer, C., Wüthrich, P., & Notter, B.: Handbook Emission Factors for Road Transport, version 4.1 (Handbuch Emissionsfaktoren des Straßenverkehrs 4.1) URL: <http://www.hbefa.net/e/index.html> - Dokumentation, Bern, 2017. : 3 : EMEP/EEA, 2019: EMEP/EEA air pollutant emission inventory guidebook 2019; <https://www.eea.europa.eu/publications/emep-eea-guidebook-2019/part-b-sectoral-guidance-chapters/1-energy/1-a-combustion/1-a-3-b-i/view>; Copenhagen, 2019. : 4 : Rentz et al., 2008: Nationaler Durchführungsplan unter dem Stockholmer Abkommen zu persistenten organischen Schadstoffen (POPs), im Auftrag des Umweltbundesamtes, FKZ 205 67 444, UBA Texte | 01/2008, January 2008 - URL: <http://www.umweltbundesamt.de/en/publikationen/nationaler-durchfuehrungsplan-unter-stockholmer> **bibliography**

¹⁾ (bibcite 1)

²⁾ (bibcite 1)

³⁾ (bibcite 2)

⁴⁾ (bibcite 1)

⁵⁾ (bibcite 3)

⁶⁾ (bibcite 4)

¹⁾

During test-bench measurements, temperatures are likely to be significantly higher than under real-world conditions, thus reducing condensation. On the contrary, smaller dilution (higher number of primary particles acting as condensation germs) together with higher pressures increase the likeliness of condensation. So over-all condensables are very likely to occur but different to real-world conditions.