# **1.A.3.b i - iv - Emissions from fuel combustion in Road** Vehicles (OVERVIEW)

## Short description

This overview chapter provides information on the emissions from fuel combustion activities in road transport sub-categories 1.A.3.b i, ii, iii, and iv.

NFR-Code	Name of Category
1.A.3.b i	Passenger Cars
1.A.3.b ii	Light Duty Vehicles
1.A.3.b iii	Heavy Duty Vehicles
1.A.3.b iv	Mopeds & Motorcycles

## Methodology

### Activity data

Basically, total inland fuel deliveries are available from the National Energy Balances (NEBs) (AGEB, 2021)<sup>1)</sup>, line 62: Straßenverkehr (Road Transport) as compiled by the Association of the German Petroleum Industry (MWV)<sup>2)</sup>.

Based upon these primary activity data, specific consumption data for the different types of road vehicles are generated within TREMOD  $^{3)}$ .



For further details see main chapter 1.A.3.b - Road Transport as wells as the sub-category chapters linked above.

#### **Emission factors**

The majority of emissions factors for exhaust emissions from road transport are taken from the 'Handbook Emission Factors for Road Transport' (HBEFA, version 4.1)<sup>4)</sup> where they are provided on a tier3 level mostly and processed within the TREMOD software used by the party<sup>5)</sup>.



With respect to the emission factors applied for particulate matter, given the circumstances during test-bench measurements, condensables are most likely included at least partly. <sup>1)</sup>

As it is not possible to present these tier3 values in a comprehendible way, the NFR sub-chapters linked above provide sets of fuel-specific implied emission factors instead.

For heavy-metal (other then lead from leaded gasoline) and PAH exhaust-emissions, default emission factors from (EMEP/EEA, 2019) <sup>6)</sup> have been applied. Regarding PCDD/F, tier1 EF from (Rentz et al., 2008) <sup>7)</sup> are used instead.



For information on the **emission factors for heavy-metal and POP exhaust emissions**, please refer to Appendix 2.3 - Heavy Metal (HM) exhaust emissions from mobile sources and Appendix 2.4 - Persistent Organic Pollutant (POP) exhaust emissions from mobile sources.

### Trends of exhaust emissions from road transport vehicles

For **ammonia emissions**, the increasing use of catalytic converters in gasoline driven cars in the 1990s lead to a steep increase whereas both the technical development of the converters and the ongoing shift from gasoline to diesel cars resulted in decreasing emissions in the following years.

The observed trends for **NO**<sub>x</sub>, **NMVOC and CO emissions** represent the changes in legislatory emission limits and the regarding implementation of mitigation technologies.

#### Table 1: Overview of Euro norms

	Type Approval for new vehicle types	Type Approval for new vehicles	Testing Cycle				
PASSENGER CARS & LIGHT-DUYT VEHICLES: DIESEL							
Euro Norm 1	since 01. Juli 1992	since 01. Januar 1993	NEFZ				
Euro 2	since 01. Januar 1996	since 01. Januar 1997	NEFZ				
Euro 3	since 01. Januar 2000	since 01. Januar 2001	NEFZ				
Euro 4	since 01. Januar 2005	since 01. Januar 2006	NEFZ				
Euro 5a	since 01. September 2009	since 01. Januar 2011	NEFZ				
Euro 5b	since 01. September 2011	since 01. Januar 2013	NEFZ				
Euro 6b	since 01. September 2014	since 01. September 2015	NEFZ				
Euro 6c	since 01. September 2017	since 01. September 2018	WLTC				
Euro 6d-Temp	since 01. September 2017	since 01. September 2019	WLTC				
Euro 6d	Freiwillige Einstufung	Freiwillige Einstufung	WLTC				
Euro 6d-ISC-FCM	since 01.01.2020 (36AP) / 10.01.2021 (36AQ- AR)	Ab 01.01.2021 (36AP) / 01.01.2022 (36AQ-AR)	WLTC				
	PASSENGER CARS & LIGHT-DUYT VEHICLES: GASOLINE						
Abgasnorm Euro 1	since 01. Juli 1992	since 01. Januar 1993					
Euro 2	since 01. Januar 1996	since 01. Januar 1997	NEFZ				
Euro 3	since 01. Januar 2000	since 01. Januar 2001	NEFZ				
Euro 4	since 01. Januar 2005	since 01. Januar 2006	NEFZ				
Euro 5a	since 01. September 2009	since 01. Januar 2011	NEFZ				
Euro 6b	since 01. September 2014	since 01. September 2015	NEFZ				
Euro 6c	since 01. September 2017	since 01. September 2018	WLTC				
Euro 6d-Temp	since 01. September 2017	since 01. September 2019	WLTC				
Euro 6d	Freiwillige Einstufung	Freiwillige Einstufung	WLTC				
Euro 6d-ISC-FCM	since 01.01.2020 (36AP) / 10.01.2021 (36AQ- AR)	Ab 01.01.2021 (36AP) / 01.01.2022 (36AQ-AR)	WLTC				
MOPEDS							
Euro 1	since 17. Juni 1999		ECE R47				
Euro 2	since 17. Juni 2002		ECE R47				
Euro 4	since 01. Januar 2017	since 01. Januar 2018	ECE R47				
Euro 5	since 01. Januar 2020	since 01. Januar 2021	WMTC				
MOTORCYCLES							
Euro 1	since 17. Juni 1999		ECE R47				
Euro 2	since 17. Juni 2002		ECE R47				
<b>BUSES &amp; TRUCKS</b>							
Euro I	01. Jan 92		ESC R-49				
Euro II	01. Okt 96		ESC R-49				
Euro III	01. Okt 00		ESC&ELR, ETC				
Euro IV	01. Okt 05		ESC&ELR, ETC				
Euro V	01. Okt 08		ESC&ELR, ETC				
Euro VI	01. Okt 13		WHTC, WHSC				

Trends for **sulphur dioxide** show charcteristics very different from those shown above. Here, the strong dependence on increasing fuel qualities leads to an cascaded downward trend of  $SO_2$  emissions, influenced only slightly by increases in fuel consumption and mileage.

The following table provides the development of sulphur contents over the years for Old (OGL) and New German Länder (NGL) and Germany (GER).

Area covered	Year(s) covered	Gasoline	Diesel oil	
EAST GERMANY (DDR)	until 1988	500 ppm	6,000 ppm	
EAST GERMANT (DDR)	1989-1990	500 ppm	6,000 ppm	
WEST GERMANY (BRD)	until 1984		2,700 ppm	
	1985		2,500 ppm	
	1986	250 ppm	2,100 ppm	
	1987	230 ppm	2,100 ppm	
	1988		1,700 ppm	
	1989			
	1990	220 ppm		
	1991		1,300 ppm	
	1992	220 nnm		
	1993	220 ppm		
GERMANY	1994			
	1995			
	1996	180 ppm	600 ppm	
	1997		400 ppm	
	1998-2000	70 ppm	300 ppm	
	2001	55 ppm	250 ppm	
	2002	25 ppm	40 ppm	
	since 2003	8 ppm	8 ppm	

Table 2: Development of fuel sulphur contents in Germany

For **exhaust particulate matter emissions** from diesel road vehicles, the party assumes that nearly all particles emitted are within the  $PM_{2.5}$  range, resulting in similar emission values for  $PM_{2.5}$ ,  $PM_{10}$ , and TSP. Excumptions from this assumption can be observed for gasoline road vehicles for the years until 1997 when **additional TSP emissions** resulted **from the use of leaded gasoline** that was banned in 1997. Furthermore, **black carbon** emissions are estimated via implied emission factors derived from fractions of PM as provided in <sup>8)</sup>.

For **Heavy Metals** and **PAHs**, emissions are calculated with tier1 default EF from <sup>9)</sup> resulting in trends that simply reflect the annual fuel consumption.

Category	Pb	Cd	Cu	Cr	Ni	Se	Zn	Hg	As
Passenger cars, petrol	0.0016	0.0002	0.0045	0.0063	0.0023	0.0002	0.033	0.0087	0.0003
Passenger cars, diesel	0.0005	5 E-05	0.0057	0.0085	0.0002	0.0001	0.018	0.0053	0.0001
LCVs, petrol	0.0016	0.0002	0.0045	0.0063	0.0023	0.0002	0.033	0.0087	0.0003
LCVs, diesel	0.0005	5 E-05	0.0057	0.0085	0.0002	0.0001	0.018	0.0053	0.0001
HDVs, petrol	0.0016	0.0002	0.0045	0.0063	0.0023	0.0002	0.033	0.0087	0.0003
HDVs, diesel	0.0005	5 E-05	0.0057	0.0085	0.0002	0.0001	0.018	0.0053	0.0001
L-category	0.0016	0.0002	0.0045	0.0063	0.0023	0.0002	0.033	0.0087	0.0003

#### Table 3-86: Heavy metal emission factors for all vehicle categories in ppm/wt fuel

Here, the only excumption are **lead emissions from leaded gasoline** that was in use until 1996 with lead contents provided in the table below:

Table 3: Development of gasoline's lead content in Germany

Area covered	Year(s) covered	Lead content
EAST GERMANY (GDR)	1989-1990	126 mg/l
WEST GERMANY (BRD)	1990	42 mg/l

Area covered	Year(s) covered	Lead content
GERMANY	1991	29 mg/l
	1992	20 mg/l
	1993	16 mg/l
	1994	11 mg/l
	1995	8 mg/l
	1996	4 mg/l
	since 1997	0 mg/l (banned)

### Recalculations

Recalculations of exhaust-emissions are mainly based on annual routine revisions of the underlying TREMOD model. For more information, please see the specific chapters linked above.

 <sup>1)</sup> AGEB (2021): Working Group on Energy Balances (Arbeitsgemeinschaft Energiebilanzen (Hrsg.), AGEB): Energiebilanz für die Bundesrepublik Deutschland; URL: https://ag-energiebilanzen.de/7-0-Bilanzen-1990-2019.html, Köln & Berlin, 2021.
<sup>2)</sup> MWV (2021): Association of the German Petroleum Industry (Mineralölwirtschaftsverband, MWV): Annual Report 2019,

page 65, Table 'Sektoraler Verbrauch von Dieselkraftstoff 2012-2019'; URL:

https://www.mwv.de/wp-content/uploads/2020/09/MWV\_Mineraloelwirtschaftsverband-e.V.-Jahresbericht-2020-Webversion.p df, Berlin, 2020.

<sup>3), 5)</sup> Knörr et al. (2021a): Knörr, W., Heidt, C., Gores, S., & Bergk, F.: ifeu Institute for Energy and Environmental Research (Institut für Energie- und Umweltforschung Heidelberg gGmbH, ifeu): Fortschreibung des Daten- und Rechenmodells: Energieverbrauch und Schadstoffemissionen des motorisierten Verkehrs in Deutschland 1960-2035, sowie TREMOD, im Auftrag des Umweltbundesamtes, Heidelberg & Berlin, 2020.

<sup>4)</sup> Keller et al. (2017): Keller, M., Hausberger, S., Matzer, C., Wüthrich, P., & Notter, B.: Handbook Emission Factors for Road Transport, version 4.1 (Handbuch Emissionsfaktoren des Straßenverkehrs 4.1) URL: http://www.hbefa.net/e/index.html -Dokumentation, Bern, 2017.

<sup>6), 8), 9)</sup> EMEP/EEA, 2019: EMEP/EEA air pollutant emission inventory guidebook 2019;

https://www.eea.europa.eu/publications/emep-eea-guidebook-2019/part-b-sectoral-guidance-chapters/1-energy/1-a-combust ion/1-a-3-b-i/view; Copenhagen, 2019.

<sup>7)</sup> Rentz et al., 2008: Nationaler Durchführungsplan unter dem Stockholmer Abkommen zu persistenten organischen Schadstoffen (POPs), im Auftrag des Umweltbundesamtes, FKZ 205 67 444, UBA Texte | 01/2008, January 2008 - URL: http://www.umweltbundesamt.de/en/publikationen/nationaler-durchfuehrungsplan-unter-stockholmer

During test-bench measurements, temperatures are likely to be significantly higher than under real-world conditions, thus reducing condensation. On the contrary, smaller dillution (higher number of primary particles acting as condensation germs) together with higher pressures increase the likeliness of condensation. So over-all condensables are very likely to occur but different to real-world conditions.