

## 2.A.5.b - Construction and Demolition

### Short description

Method	AD	EF	Key Category
T1	NS	CS	<b>L&amp;T:</b> TSP, PM <sub>10</sub>

**T** = key source by Trend **L** = key source by Level

Methods	
<b>D</b>	Default
<b>T1</b>	Tier 1 / Simple Methodology *
<b>T2</b>	Tier 2*
<b>T3</b>	Tier 3 / Detailed Methodology *
<b>C</b>	CORINAIR
<b>CS</b>	Country Specific
<b>M</b>	Model

\* as described in the EMEP/EEA Emission Inventory Guidebook - 2019, in the group specific chapters.

AD - Data Source for Activity Data	
<b>NS</b>	National Statistics
<b>RS</b>	Regional Statistics
<b>IS</b>	International Statistics
<b>PS</b>	Plant Specific data
<b>As</b>	Associations, business organisations
<b>Q</b>	specific Questionnaires (or surveys)
<b>M</b>	Model / Modelled
<b>C</b>	Confidential

  

EF - Emission Factors	
<b>D</b>	Default (EMEP Guidebook)
<b>C</b>	Confidential
<b>CS</b>	Country Specific
<b>PS</b>	Plant Specific data
<b>M</b>	Model / Modelled

Information about the key source relevance can be found in [2.A - Mineral Industry](#). For particulate emissions, Construction is the main emissions source in the Mineral industries.

### Methodology

Since the last update of the UNECE Guidebook we use the Tier 1 method to estimate the national emissions of particulate matters. The approach for uncontrolled fugitive emissions for this source category was adapted for national circumstances within a research Project (Umweltbundesamt, 2016) <sup>1)</sup>, partly considered existing control techniques. As a result, the information of the statistics is combined with modified default emission factors for TSP and PM.

### Activity data

Activity data are determined taking into account figures for various construction activities. Data is based on production statistics (national statistics). According to the method used, figures of area of land affected by construction activities per building were concluded from statistical data and multiplied with emission factors, as explained below. The common uncertainty of 3% for national statistics could be increased as a result of this calculation, but the effect is not estimated at the moment.

## Emission factors

The emission factors used are results of Adaptation of UNECE-Defaults (EEA, 2016) <sup>2)</sup>, see chapter NFR 2.A.5.b for different kind of buildings.

Table 1: Overview of applied emission factors

~ kind of building	~ pollutant	~ EF value	~ unit	~ EF trend			
single and two family houses	TSP	0.0638	kg/m	2	* y	constant	
single and two family houses	PM <sub>10</sub>	0.0191	kg/m	2	* y	constant	
single and two family houses	PM <sub>2.5</sub>	0.0019	kg/m	2	* y	constant	
apartment buildings	TSP	0.329	kg/m	2	* y	constant	
apartment buildings	PM <sub>10</sub>	0.099	kg/m	2	* y	constant	
apartment buildings	PM <sub>2.5</sub>	0.0099	kg/m	2	* y	constant	
non-residential	TSP	0.631	kg/m	2	* y	constant	
non-residential	PM <sub>10</sub>	0.189	kg/m	2	* y	constant	
non-residential	PM <sub>2.5</sub>	0.0189	kg/m	2	* y	constant	
roads	TSP	1,674	t/km	2	* y	constant	
roads	PM <sub>10</sub>	502	t/km	2	* y	constant	
roads	PM <sub>2.5</sub>	50.2	t/km	2	* y	constant	

Several further assumptions were necessary to use the formula of the Guidebook:

$$\sim EM = EF * B * f * m$$

The EF is adapted with Moisture Level Correction factor and Silt Content Correction factor in all cases, both 0.20 and 2.22. The assumption about the duration of the construction activity uses the Default values.

~ Type of building	~ Estimated duration (year)
Construction of houses (single and two family)	0.5 (6 months)
Construction of apartments (all types)	0.75 (9 months)
Non-residential construction	0.83 (10 months)
Road construction	1 (12 months)

Source (EEA, 2016) <sup>3)</sup>

AD is a result of multiplying B the number of houses constructed and f the conversion factor.

### + Trends in emissions

All trends in emissions as product of EF and AD correspond to trends of construction activities.

[gallery size="medium" viewer="yes" : EM\\_2A5b\\_since\\_1990.PNG gallery](#)

### + Recalculations

With **activity data** and **emission factors** remaining unrevised, no recalculations have been carried out compared to last year's submission.



For pollutant-specific information on recalculated emission estimates for Base Year and 2018, please see the pollutant specific recalculation tables following [chapter 8.1 - Recalculations](#).

## Planned improvements

At the moment, no category-specific improvements are planned.

## FAQs

**Where can I find emissions estimation of demolition activities?** - Demolishing without any significant new construction is not covered and there are no other emission factors available for demolition activities only. Nevertheless you can find Information about emissions from [buildings fires](#)].

**Why do German EFs differ from EEA defaults?** - It has to do with the default 50% reduction for non-residential buildings and roads (as a result of wetting unpaved temporary roads) that is assumed in the calculations for Germany. This is also already accounted for in the EPA emission factors. It is a result of a control measure that is nearly always taken but in principle optional. In the Guidebook a 50% reduction is advised.

---

**bibliography** : 1 : Umweltbundesamt, 2016: Development of Methods for the Generation of Emission Data for Air Pollutants from Building Activity and Construction Zones, Dessau-Roßlau, 2016; [!-URL: <http://webde/gruppen/bibliothek/OnlineReports/EF000592.pdf>--] **Document (PDF)** : 2 : EEA, 2016: EEA Report No 21/2016 EMEP EEA air pollutant emission inventory guidebook 2016, Copenhagen, 2016; URL: [https://www.eea.europa.eu/ds\\_resolveuid/EJ6RT9P2Y3](https://www.eea.europa.eu/ds_resolveuid/EJ6RT9P2Y3)

**bibliography**

---

<sup>1)</sup> (bibcite 1)

<sup>2)</sup> (bibcite 2)

<sup>3)</sup> (bibcite 2)